

BUSHING/HOUSING - COPPER ALLOY, NICKEL PLATED INSULATOR - THERMOPLASTIC, BLACK TERMINALS - COPPER ALLOY, MATTE TIN PLATED CENTER CONTACT PIN - COPPER ALLOY, GOLD PLATED SLEEVE CONTACT - COPPER ALLOY, GOLD PLATED O-RINGS - THERMOPLASTIC RUBBER HEX NUT - COPPER ALLOY, NICKEL PLATED WASHER - STEEL, NICKEL PLATED

2. THIS PRODUCT IS RoHS COMPLIANT.

| | | | | | | THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY. | | | | | | | | | |
|-----------|------------|----------|----------|----------|--------------------------------------|--|------------|---------|----------|-------------|---------|---------|------|----|-----|
| | | | <u> </u> | | UNLESS OTHERWISE SPECIFIED | SIZE | E WIDTH MU | | MULT | | LBS/M | S/M TEN | | ER | |
| | | | | | 1. ALL DIMENSIONS IN INCHES [mm] | FINISH SPEC No. | | | | MATERIAL | | | | | |
| | | | | | - TWO PLACE DECIMALS ±0.02 [0.5] | | | | | SPEC No. | | | | | |
| | | + | | \vdash | 1 | FIRST USED ON | | N : | SCALE | | | | | | |
| | | | I | | - THREE PLACE DECIMALS ±0.005 [0.13] | | | | 3:1 | -Swileheral | | | 317° | | |
| | | | | | | DATE DRAWN | BY | CHKD | APVD | | | | | | |
| | | | | | | 0.06.40 | SRC | SRC | SRC | | | | | | |
| Α | 27391 | 11-10-14 | PC | TJK | | 9-26-13 | SKC | 9-26-13 | 11-10-14 | | SHEET 1 | (| OF | 1 | |
| REV | ECO NUMBER | DATE | BY | APVD | | NAME STRAIGHT SEALED | | | | PART No | | | | | REV |
| REVISIONS | | | | | DO NOT SCALE DRAWING | 10 AMP POWER JACK, RoHS | | | | ST10U / | | | | Α | |

SolidWorks CAD File B